



# ATG® DYNEEMA® DIAMOND GLOVES

PRODUCT INFORMATION



## ATG® cut protection

**DURABLE, EXTENDED WEAR FOR IMPROVED PERFORMANCE**

- ATG MaxiFlex® Cut™ / MaxiCut® Ultra™ feature Dyneema® Diamond Technology, a highly durable lightweight fiber that provides excellent abrasion resistance, and tactile sensitivity.
- Embedded micro-particles in the Dyneema® fiber provide additional cut resistance. The patented Nitrile Microfoam coating offers 360° breathability and cool touch comfort to improve worker productivity.
- Built strong for applications that require a solid grip in wet and dirty conditions, including a reinforced thumb and forefinger for extended glove life in an inherently weak area.



# ATG® DYNEEMA® DIAMOND GLOVES

PRODUCT INFORMATION

ANSI  
**A2**



◀ 34-6743

ANSI  
**A3**



◀ 44-6745

## PRODUCT DESCRIPTION

**KNOWN ACROSS THE GLOBE, ATG® MAXIFLEX® AND MAXICUT® HAVE BECOME THE WORLD STANDARD FOR PRECISION HANDLING GLOVES.**

MaxiFlex® Cut™ / MaxiCut® Ultra™ seamless knit gloves with integrated Dyneema® Diamond fiber blend are extremely durable for extended glove life. The MaxiFlex® Cut™ ANSI A2 is built for light duty jobs that require high dexterity. The MaxiCut® Ultra™ will handle medium duty applications that require more abrasion resistance.

Both glove styles feature a super light-weight and thin liner with 360° breathability with integrated ATG® patented AIRtech® Nitrile Microfoam Coating that swiftly evacuates heat that builds up inside the glove.

## APPLICATIONS

- Sorting and handling
- Anchoring and fastening
- Clamping and hoisting material
- Handling or repair of sharp parts
- Mounting and equipment assembly
- Threading and pipework



## PERFORMANCE

### 34-6743 PERFORMANCE PROPERTIES

**EN388: 4X32B** ASTM F2992-15 ANSI Cut Level **A2** (Adopted by ANSI/ISEA 02/16)

ABRASION	0	1	2	3	<b>4</b>	
CUT	<b>X</b>	1	2	3	4	5
TEAR	0	1	2	<b>3</b>	4	
PUNCTURE	0	1	<b>2</b>	3	4	
CUT (TDM-100)	A	<b>B</b>	C	D	E	F

### 44-6745 PERFORMANCE PROPERTIES

**EN388: 4X43C** ASTM F2992-15 ANSI Cut Level **A3** (Adopted by ANSI/ISEA 02/16)

ABRASION	0	1	2	3	<b>4</b>	
CUT	<b>X</b>	1	2	3	4	5
TEAR	0	1	2	3	<b>4</b>	
PUNCTURE	0	1	2	<b>3</b>	4	
CUT (TDM-100)	A	B	<b>C</b>	D	E	F

**ATG® TECHNOLOGY MAKES IT HAPPEN**



**CUTtech®** – Innovative fibers we source our base ingredients to develop our own unique high performance yarns and fibres that offer cut protection while maintaining high levels of comfort.

All ATG Gloves are laundered before they are packaged making them clean and skin safe. They are REACH compliant, certified by the Oeko-Tex Association, and accredited by the Skin Health Alliance.

ITEM NUMBER	ANSI	EN 388	COATING	COATING COVERAGE	COATING COLOR	LINER MATERIAL	LINER COLOR	SIZES
34-6743	A2	4X32B	Nitrile Coated MicroFoam	Palm & Fingers	■ Black	Dyneema® Diamond	■ Green	S - 2XL
44-6745	A3	4X43C	Nitrile Coated MicroFoam	Palm & Fingertips	■ Black	Dyneema® Diamond	■ Blue	S - 2XL

