



# SPECIFICATION SHEET

## 263-43003

### SECURE™ 3 PASSIVE EAR MUFFS - NECKBAND

- Ideal for use in conjunction with bump caps, hard hats without universal slots or head mounted face protection
- Offered in three protection levels, clearly indicated with bright safety-colored spacers for easy identification
- Head support strap is adjustable and ensures muffs stay in position at all times
- Strong and flexible neckband balances the weight over the neck, keeping an even pressure over the ears
- Slim profile design increases stability and reduces risk of snagging in confined spaces
- Soft and wide ear cushions feature snap-in system for easy replacement
- Dielectric, non-conductive

### APPLICATIONS

- Low frequency noise
- Airport ground crew
- Motor racing
- Drill hammering

### TECHNICAL DATA

MATERIAL	<b>Ear Cups and Spacer:</b> ABS thermoplastic <b>Ear Cushion:</b> Polyether & PVC-foil <b>Foam liner:</b> Polyether <b>Textile headband:</b> Nylon with velcro <b>Neckband attachment:</b> POM thermoplastic <b>Neckband:</b> Electric insulated stainless steel
COLOR	Orange / Black
ATTENUATION	NRR: 27 dB / SNR: 33 dB
STYLE	Neckband
SIZE	Adjustable
WEIGHT	8.5 oz / 240 g
PACKAGING	20 per case
CASE	22" x 14" x 13" / 56cm x 36cm x 33cm
CASE WEIGHT	16.5 lbs / 7.5 kg
COO	Sweden

### BARCODES

ITEM	EACH	DOZEN	CASE
263-43003	7391441000371	---	7391441000371



### ATTENUATION DATA

FREQUENCY HZ	125	250	500	1000	2000	3150	4000	6300	8000	NRR
Mean Attenuation dB	18.9	22.8	32.2	41.8	36.8	35.9	37.6	39.4	38.3	27
Standard Deviation dB	2.9	2.2	2.2	2.7	2.7	2.3	2.4	2.8	3.2	

Tested in accordance with ANSI standard S3.19-1974

Canada Class A (L)

FREQUENCY HZ	63	125	250	500	1000	2000	4000	8000	H	M	L	SNR
Mean Attenuation dB	18,1	18,7	25,2	32,2	42,6	36,1	38,9	38,0				33
Standard Deviation dB	5,8	4,3	2,7	3,1	4,1	2,7	3,4	4,5	35	31	22	
APV dB	12,3	14,4	22,5	29,1	38,5	33,4	35,5	33,5				