

# SPECIFICATION SHEET

STYLE: 34-8753V



#### MaxiFlex® Cut™

Seamless Knit Engineered Yarn Glove with Premium Nitrile Coated MicroFoam Grip on Palm, Fingers & Knuckles - Vend-Ready

- MicroFoam Nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Knit Wrist helps prevent dirt and debris from entering the glove
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Innovative fibres we source our base ingredients to develop our own unique high performance yarns and fibres that offer cut protection whilst maintaining high levels of comfort.
- Reinforcement between the thumb and forefinger, improves cut resistance and extends glove life in an inherently weak area.
- 360° breathability patented micro-foam nitrile coating offers 360° breathability, making it the most breathable glove on the market today.













#### **Technical Data**

| Color                | Green   |
|----------------------|---|
| Sizes Available      | XS-3XL  |
| Packaging            | Bulk Pack   |
| Packed               | 72 Pair/Case  |
| Case Dimensions (in) | 7.87 x 11.61 x 19.69  |
| Case Weight (lbs)    | 0.00  |
| Country of Origin    | Sri Lanka   |
| Liner Material       | Engineered Yarn   |
| Coating              | Nitrile   |
| Coating Color        | Black   |
| Coating Coverage     | Palm, Fingers & Knuckles  |
| Grip                 | MicroFoam   |
| Gauge                | 15  |
| Cuff                 | Knit Wrist  |
| Impact Protection    |   |
| Construction         | Coated Seamless Knit,<br>Reinforced Thumb Crotch,<br>Touchscreen Compatible |
| Certifications       | 21 CFR, Silicone Free, Latex Free   |
| Product Circularity  | Reusable / Launderable<br>Recycled via Terracycle                           |

#### **Performance Data**

| ANSI Cut Level                  | A2     |
|---------------------------------|--------|
| ANSI Abrasion Level             | 3      |
| ANSI Puncture Level             |        |
| ANSI Impact Level               |        |
| ANSI Contact Heat Level         |        |
| EN 388                          | 4331BX |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          |        |



## SPECIFICATION SHEET

STYLE: 34-8753V

### **SKU Information**

| SKU           | COLOR | SIZE | UPC          | UPC (INNER)    | UPC (CASE)     |
|---------------|-------|------|--------------|----------------|----------------|
| 34-8753V/XS   | Green | XS   | 616314211508 | 01616314211507 | 02616314211506 |
| 34-8753V/S    | Green | S    | 616314211485 | 01616314211484 | 02616314211483 |
| 34-8753V/M    | Green | М    | 616314211478 | 01616314211477 | 02616314211476 |
| 34-8753V/L    | Green | L    | 616314211461 | 01616314211460 | 02616314211469 |
| 34-8753V/XL   | Green | XL   | 616314211492 | 01616314211491 | 02616314211490 |
| 34-8753V/XXL  | Green | 2XL  | 616314211515 | 01616314211514 | 02616314211513 |
| 34-8753V/XXXI | Green | 3XI  | 616314696428 | 10616314696425 | 20616314696422 |