



Technical Data

Color	Black
Sizes Available	M7-M15
Packaging	Boxed
Packed	10 Pair/Case
Case Dimensions (in)	25.39 x 17.72 x 13.39
Case Weight (lbs)	33.07
Material	Leather
Outsole	--
Toe Type	Composite
Tread Pattern	--
Height	--
Construction	Slip Resistant
Certifications	TAA Compliant, ASTM F2413-18
Product Circularity	--

PUMA® Safety

Iconic Black LOW Composite Toe Impact Resistant Toe Cap, Static Dissipating safety, Slip Resistant, Safety Shoes

- RUBBER SOLE HERITAGE - The 572°F heat-resistant rubber outsole has an excellently slip resistant herringbone pattern with optimum grip. The softer rubber midsole grants underfoot cushioning and shock absorption. By increasing the rotation point, friction and thus fatigue are greatly reduced. The wide frame ensures all around perfect stabilization.
- idCELL - The idCELL element in the heel area consists of EVA, a very soft, shock absorbing material. It perfectly absorbs impacts and shocks when the heel strikes the ground.
- ROTATION POINT - The special feature of the sole is the integrated rotation point. This point in the area of the inner metatarsus is the most severely strained part while walking. By reinforcing the rotation point, friction and thus fatigue is greatly reduced.
- EVERCUSHION® RELIEF - Maximum performance for your work shoes. The contoured evercushion® RELIEF footbed follows the shape of the foot and ensures pressure relief. A specially coordinated arch support enables the foot to be positioned naturally in the shoe and stimulates the muscles when walking. A layer of a particularly soft and stable foam provides extra cushioning and thus superior shock absorption. Grooves on the underside of the insole ensure that the sole does not slip in the shoe. Comfort and support to get your job done.

Performance Data

ASTM F2413 Requirement	--Compression Resistance-- Impact Resistance--Static Dissipative Properties--
------------------------	---

Care Instructions



Hand Wash



SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
640005-07-200	Black	M7	885818016333		20885818016337
640005-07.5-200	Black	M7.5	885818016340		20885818016344
640005-08-200	Black	M8	885818016357		20885818016351
640005-08.5-200	Black	M8.5	885818016364		20885818016368
640005-09-200	Black	M9	885818016371		20885818016375
640005-09.5-200	Black	M9.5	885818016388		20885818016382
640005-10-200	Black	M10	885818016395		20885818016399
640005-10.5-200	Black	M10.5	885818016401		20885818016405
640005-11-200	Black	M11	885818016418		20885818016412
640005-11.5-200	Black	M11.5	885818016425		20885818016429
640005-12-200	Black	M12	885818016432		20885818016436
640005-13-200	Black	M13	885818016449		20885818016443
640005-14-200	Black	M14	885818016456		20885818016450
640005-15-200	Black	M15	885818016463		20885818016467