



### Technical Data

Color	Blue
Sizes Available	M7-M15
Packaging	Boxed
Packed	10 Pair/Case
Case Dimensions (in)	25.39 x 17.72 x 13.39
Case Weight (lbs)	32.63
Material	Suede
Outsole	--
Toe Type	Composite
Tread Pattern	--
Height	--
Construction	Slip Resistant
Certifications	TAA Compliant, ASTM F2413-18
Product Circularity	--

### PUMA® Safety

Iconic Suede Navy LOW Composite Toe Impact Resistant Toe Cap, Electrical Hazard protection, Slip Resistant, Safety Shoes

- **RUBBER SOLE HERITAGE** - The 572°F heat-resistant rubber outsole has an excellently slip resistant herringbone pattern with optimum grip. The softer rubber midsole grants underfoot cushioning and shock absorption. By increasing the rotation point, friction and thus fatigue are greatly reduced. The wide frame ensures all around perfect stabilization.
- **idCELL** - The idCELL element in the heel area consists of EVA, a very soft, shock absorbing material. It perfectly absorbs impacts and shocks when the heel strikes the ground.
- **ROTATION POINT** - The special feature of the sole is the integrated rotation point. This point in the area of the inner metatarsus is the most severely strained part while walking. By reinforcing the rotation point, friction and thus fatigue is greatly reduced.
- **EVERCUSHION® RELIEF** - Maximum performance for your work shoes. The contoured evercushion® RELIEF footbed follows the shape of the foot and ensures pressure relief. A specially coordinated arch support enables the foot to be positioned naturally in the shoe and stimulates the muscles when walking. A layer of a particularly soft and stable foam provides extra cushioning and thus superior shock absorption. Grooves on the underside of the insole ensure that the sole does not slip in the shoe. Comfort and support to get your job done.

### Performance Data

ASTM F2413 Requirement	--Compression Resistance-- Electrical Hazard Resistance-- Impact Resistance--
------------------------	---

### Care Instructions



Hand Wash



## SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
640025-07-300	Blue	M7	885818016616		20885818016610
640025-07.5-300	Blue	M7.5	885818016623		20885818016627
640025-08-300	Blue	M8	885818016630		20885818016634
640025-08.5-300	Blue	M8.5	885818016647		20885818016641
640025-09-300	Blue	M9	885818016654		20885818016658
640025-09.5-300	Blue	M9.5	885818016661		20885818016665
640025-10-300	Blue	M10	885818016678		20885818016672
640025-10.5-300	Blue	M10.5	885818016685		20885818016689
640025-11-300	Blue	M11	885818016692		20885818016696
640025-11.5-300	Blue	M11.5	885818016708		20885818016702
640025-12-300	Blue	M12	885818016715		20885818016719
640025-13-300	Blue	M13	885818016722		20885818016726
640025-14-300	Blue	M14	885818016739		20885818016733
640025-15-300	Blue	M15	885818016746		20885818016740