



PUMA® Safety

Iconic Suede Grey LOW Composite Toe Impact Resistant Toe Cap, Static Dissipating safety, Slip Resistant, Safety Shoes

- **RUBBER SOLE HERITAGE** - The 572°F heat-resistant rubber outsole has an excellently slip resistant herringbone pattern with optimum grip. The softer rubber midsole grants underfoot cushioning and shock absorption. By increasing the rotation point, friction and thus fatigue are greatly reduced. The wide frame ensures all around perfect stabilization.
- **idCELL** - The idCELL element in the heel area consists of EVA, a very soft, shock absorbing material. It perfectly absorbs impacts and shocks when the heel strikes the ground.
- **ROTATION POINT** - The special feature of the sole is the integrated rotation point. This point in the area of the inner metatarsus is the most severely strained part while walking. By reinforcing the rotation point, friction and thus fatigue is greatly reduced.
- **EVERCUSHION® RELIEF** - Maximum performance for your work shoes. The contoured evercushion® RELIEF footbed follows the shape of the foot and ensures pressure relief. A specially coordinated arch support enables the foot to be positioned naturally in the shoe and stimulates the muscles when walking. A layer of a particularly soft and stable foam provides extra cushioning and thus superior shock absorption. Grooves on the underside of the insole ensure that the sole does not slip in the shoe. Comfort and support to get your job done.

Technical Data

Color	Gray
Sizes Available	M7-M15
Packaging	Boxed
Packed	10 Pair/Case
Case Dimensions (in)	25.39 x 17.72 x 13.39
Case Weight (lbs)	31.53
Material	Suede
Outsole	--
Toe Type	Composite
Tread Pattern	--
Height	--
Construction	Slip Resistant
Certifications	TAA Compliant, ASTM F2413-18
Product Circularity	--

Performance Data

ASTM F2413 Requirement	--Compression Resistance-- Impact Resistance--Static Dissipative Properties--
------------------------	---

Care Instructions



Hand Wash



SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
640035-07-800	Gray	M7	885818016753		20885818016757
640035-07.5-800	Gray	M7.5	885818016760		20885818016764
640035-08-800	Gray	M8	885818016777		20885818016771
640035-08.5-800	Gray	M8.5	885818016784		20885818016788
640035-09-800	Gray	M9	885818016791		20885818016795
640035-09.5-800	Gray	M9.5	885818016807		20885818016801
640035-10-800	Gray	M10	885818016814		20885818016818
640035-10.5-800	Gray	M10.5	885818016821		20885818016825
640035-11-800	Gray	M11	885818016838		20885818016832
640035-11.5-800	Gray	M11.5	885818016845		20885818016849
640035-12-800	Gray	M12	885818016852		20885818016856
640035-13-800	Gray	M13	885818016869		20885818016863
640035-14-800	Gray	M14	885818016876		20885818016870
640035-15-800	Gray	M15	885818016883		20885818016887