



## PUMA® Safety

Iconic Black Womens LOW Composite Toe Impact Resistant Toe Cap, Static Dissipating safety, Slip Resistant, Safety Shoes

- **RUBBER SOLE HERITAGE** - The 572°F heat-resistant rubber outsole has an excellently slip resistant herringbone pattern with optimum grip. The softer rubber midsole grants underfoot cushioning and shock absorption. By increasing the rotation point, friction and thus fatigue are greatly reduced. The wide frame ensures all around perfect stabilization.
- **idCELL** - The idCELL element in the heel area consists of EVA, a very soft, shock absorbing material. It perfectly absorbs impacts and shocks when the heel strikes the ground.
- **ROTATION POINT** - The special feature of the sole is the integrated rotation point. This point in the area of the inner metatarsus is the most severely strained part while walking. By reinforcing the rotation point, friction and thus fatigue is greatly reduced.
- **EVERCUSHION® RELIEF** - Maximum performance for your work shoes. The contoured evercushion® RELIEF footbed follows the shape of the foot and ensures pressure relief. A specially coordinated arch support enables the foot to be positioned naturally in the shoe and stimulates the muscles when walking. A layer of a particularly soft and stable foam provides extra cushioning and thus superior shock absorption. Grooves on the underside of the insole ensure that the sole does not slip in the shoe. Comfort and support to get your job done.

## Technical Data

Color	Black
Sizes Available	W5-W11
Packaging	Boxed
Packed	10 Pair/Case
Case Dimensions (in)	25.39 x 17.72 x 13.39
Case Weight (lbs)	33.73
Material	Leather
Outsole	--
Toe Type	Composite
Tread Pattern	--
Height	--
Construction	Slip Resistant
Certifications	TAA Compliant, ASTM F2413-18
Product Circularity	--

## Performance Data

ASTM F2413 Requirement	--Compression Resistance-- Impact Resistance--Static Dissipative Properties--
------------------------	---

## Care Instructions



Hand Wash



## SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
640105-05-200	Black	W5	885818017033		20885818017037
640105-05.5-200	Black	W5.5	885818017040		20885818017044
640105-06-200	Black	W6	885818017057		20885818017051
640105-06.5-200	Black	W6.5	885818017064		20885818017068
640105-07-200	Black	W7	885818017071		20885818017075
640105-07.5-200	Black	W7.5	885818017088		20885818017082
640105-08-200	Black	W8	885818017095		20885818017099
640105-08.5-200	Black	W8.5	885818017101		20885818017105
640105-09-200	Black	W9	885818017118		20885818017112
640105-09.5-200	Black	W9.5	885818017125		20885818017129
640105-10-200	Black	W10	885818017132		20885818017136
640105-11-200	Black	W11	885818017149		20885818017143