



PUMA® Safety

Iconic Suede Grey Womens LOW Composite Toe Impact Resistant Toe Cap, Static Dissipating safety, Slip Resistant, Safety Shoes

- **RUBBER SOLE HERITAGE** - The 572°F heat-resistant rubber outsole has an excellently slip resistant herringbone pattern with optimum grip. The softer rubber midsole grants underfoot cushioning and shock absorption. By increasing the rotation point, friction and thus fatigue are greatly reduced. The wide frame ensures all around perfect stabilization.
- **idCELL** - The idCELL element in the heel area consists of EVA, a very soft, shock absorbing material. It perfectly absorbs impacts and shocks when the heel strikes the ground.
- **ROTATION POINT** - The special feature of the sole is the integrated rotation point. This point in the area of the inner metatarsus is the most severely strained part while walking. By reinforcing the rotation point, friction and thus fatigue is greatly reduced.
- **EVERCUSHION® RELIEF** - Maximum performance for your work shoes. The contoured evercushion® RELIEF footbed follows the shape of the foot and ensures pressure relief. A specially coordinated arch support enables the foot to be positioned naturally in the shoe and stimulates the muscles when walking. A layer of a particularly soft and stable foam provides extra cushioning and thus superior shock absorption. Grooves on the underside of the insole ensure that the sole does not slip in the shoe. Comfort and support to get your job done.

Technical Data

Color	Gray
Sizes Available	W5-W11
Packaging	Boxed
Packed	10 Pair/Case
Case Dimensions (in)	22.44 x 17.32 x 12.99
Case Weight (lbs)	28.22
Material	Suede
Outsole	--
Toe Type	Composite
Tread Pattern	--
Height	--
Construction	Slip Resistant
Certifications	TAA Compliant, ASTM F2413-18
Product Circularity	--

Performance Data

ASTM F2413 Requirement	--Compression Resistance-- Impact Resistance--Static Dissipative Properties--
------------------------	---

Care Instructions



Hand Wash



SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
640125-05-800	Gray	W5	885818017279		20885818017273
640125-05.5-800	Gray	W5.5	885818017286		20885818017280
640125-06-800	Gray	W6	885818017293		20885818017297
640125-06.5-800	Gray	W6.5	885818017309		20885818017303
640125-07-800	Gray	W7	885818017316		20885818017310
640125-07.5-800	Gray	W7.5	885818017323		20885818017327
640125-08-800	Gray	W8	885818017330		20885818017334
640125-08.5-800	Gray	W8.5	885818017347		20885818017341
640125-09-800	Gray	W9	885818017354		20885818017358
640125-09.5-800	Gray	W9.5	885818017361		20885818017365
640125-10-800	Gray	W10	885818017378		20885818017372
640125-11-800	Gray	W11	885818017385		20885818017389