

SPECIFICATION SHEET

STYLE: 642925-200



PUMA® Safety

Celerity Knit Black LOW Steel Toe Static Dissipating safety, Safety Shoes

- RUBBER OUTSOLE This 572°F heat, oil and slip resistant rubber sole, with TPU protection in the heel area, is inspired by the latest running technology. The sole profile with it's diagonal grooves ensures a perfect flexibility and a secure contact to the ground (SRC). (ASTM F 1677 Mark II)
- TORSION CONTROL ELEMENT The TPU torsion control element in the middle of the sole supports the natural flexing action of the foot while walking and provides a better support and stability for the feet.
- EVA MIDSOLE Thousands of tiny bubbles in this ultra lightweight midsole ensure an optimal cushioning and improve the flexing action of the foot.
- IQ.CELL The gel pad directly embedded in the heel area works just like a trampoline – it absorbs shock energy and returns it immediately as bounce.
- SAFETY KNIT® STEP IN COMFORT The highly flexible fabric adapts perfectly to the foot and fits like a sock. The SAFETY KNIT® upper, a mixture of high quality synthetic fibers, offers high flexibility, resistance and breathability.
- EVERCUSHION® MISS This anatomically designed lightweight footbed with waffle structure will keep your feet cool and dry by transmitting moisture away from the foot. The open cells allow a rapid drying when the shoes have been taken off.

Technical Data

Color	Black
Sizes Available	W5-W10
Packaging	Boxed
Packed	10 Pair/Case
Case Dimensions (in)	22.44 x 17.32 x 12.99
Case Weight (lbs)	27.45
Country of Origin	China
Material	SAFETY KNIT
Outsole	
Toe Type	Steel Toe
Tread Pattern	
Height	
Construction	Slip Resistant
Certifications	ASTM F2413-18
Product Circularity	

Performance Data

ASTM F2413 Requirement

--Compression Resistance--Impact Resistance--Static Dissipative Properties--

Care Instructions



Hand Wash



SPECIFICATION SHEET

STYLE: 642925-200

SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
642925-05-200	Black	W5	885818006310		20885818006314
642925-06-200	Black	W6	885818006327		20885818006321
642925-06.5-200	Black	W6.5	885818006334		20885818006338
642925-07-200	Black	W7	885818006341		20885818006345
642925-07.5-200	Black	W7.5	885818006358		20885818006352
642925-08-200	Black	W8	885818006365		20885818006369
642925-08.5-200	Black	W8.5	885818006372		20885818006376
642925-09-200	Black	W9	885818006389		20885818006383
642925-09.5-200	Black	W9.5	885818006396		20885818006390
642925-10-200	Black	W10	885818006402		20885818006406