

## SPECIFICATION SHEET

STYLE: 647670-200



#### **Technical Data**

Color	Black
Sizes Available	
Packaging	
Packed	
Case Dimensions (in)	
Case Weight (lbs)	0.00
Country of Origin	China
Footwear Height	Low
Footwear Insole	
Footwear Width	
Gender	Men
Lining	
Material	Textile
Тое Туре	
Construction	
Certifications	
Product Circularity	

### Albatros®

Voltage Black QI LOW S1P ESD HRO SRC Composite Toe Electrostatic Dissipative Shoes, Heat Resistant, Slip Resistant, Safety Boots

- WORKLETICS 3D SOLE The core layer of the sole is the large pad made of PWR BEADS®, which extends far below the metatarsus. The upper layer, made of very light EVA material, provides dynamic cushioning with good stabilization at the same time. The right grip is guaranteed by the non-slip and abrasion-resistant, two-colour rubber outsole with wide flex grooves for optimum flexibility.
- PWR BEADS® MIDSOLE PWR BEADS® are literally baked together to form one element during the production process. Together they achieve an excellent energy return of 58%.
- FAP®LITE FLEXIBLE ANTI PENETRATION The latest generation of metal-free penetration protections: 50% lighter, very high flexibility, better cushioning and pressure elasticity, cooling effect through breathability and sweat absorption.
- evercushion® CUSTOM FIT MID The anatomically shaped evercushion® CUSTOM FIT MID footbed provides optimal cushioning positioning of the foot in the shoe and stimulates the muscles when walking. Also available in the retail pack in the Versions LOW and HIGH for narrow ones or wide feet.

#### Performance Data

ASTM F2413 Requirement

#### Care Instructions



with every step. The specially fitted arch support enables the natural



# SPECIFICATION SHEET STYLE: 647670-200

**SKU Information** 

SKU COLOR SIZE UPC UPC (INNER) UPC (CASE)