

## SPECIFICATION SHEET

STYLE: 150-2-14



#### **NOVAX®**

# Class 2 Rubber Insulating Glove with Straight Cuff - 14"

- Contoured shape reduces hand fatigue
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability
- Silicone free
- Individually numbered for traceability and stamped with factory manufacturing date
- Meets ANSI/ASTM D120 standard.

### **Applications**

- Power Generation
- Electrical Contractors
- Plant Maintenance
- Utility Work
- Hybrid Automotive Repair, Service and Manufacturing

#### **Technical Data**

d
ir/Case
x 16.93 x 19.80
ysia
per
ght
<
M D120, Silicone Free

#### **Performance Data**

Electrical Class Class 2

#### **Care Instructions**

Wash in warm water (29°C/85°F) with mild detergent and disinfect with a small amount of chlorine bleach. Air or tumble dry at low heat (74°C/165°F). Gloves may be dusted lightly with talc to reduce tackiness. Gloves should be stored in a glove bag, finger tips up, hung and not laid flat. Leather protecting glove should be removed before storage. Never fold gloves. Store in as dry and cool (35°C/95°F maximum) location as possible, away from sources of ozone and direct sunlight.



## SPECIFICATION SHEET

STYLE: 150-2-14

### **SKU Information**

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
150-2-14/7	Black	7	616314051203	01616314051202	02616314051201
150-2-14/8	Black	8	616314050916	01616314050915	02616314050914
150-2-14/8.5	Black	8.5	848309063551	10848309063558	20848309063555
150-2-14/9	Black	9	616314050923	01616314050922	02616314050921
150-2-14/9.5	Black	9.5	848309063599	10848309063596	20848309063593
150-2-14/10	Black	10	616314050930	01616314050939	02616314050938
150-2-14/10.5	Black	10.5	848309063674	10848309063671	20848309063678
150-2-14/11	Black	11	616314050947	01616314050946	02616314050945
150-2-14/12	Black	12	616314057922	01616314057884	02616314057883