



Albatros®

Lift Grey Impulse LOW S1P ESD HRO SRA
Composite Toe Electrostatic Dissipative Shoes,
Heat Resistant, Slip Resistant, Safety Boots

- **DUAL IMPULSE SLIP RESISTANT OUTSOLE** - The easy to clean rubber outsole ensures perfect ground contact. It is non-slip and abrasion resistant as well as heat resistant up to 300°C (HRO). The specially designed cleat profile and the wide flex grooves guarantee optimum flexion, optimize the water-displacing properties (windscreen wiper effect) and provide firm grip on a wide variety of grounds.
- **IMPULSE.FOAM® midsole** - Ultimate comfort during long working days. The innovative IMPULSE.FOAM® midsole in two different densities reacts to each of your steps with an energy impulse. Thereby the IMPULSE.FOAM® does not only return the energy, but also provides maximum cushioning and excellent stability.
- **comfit® AIR FOOTBED** - The newly developed, breathable ALBATROS® comfit® AIR footbed has elevations in the heel and ball area of the foot as well as a support of the longitudinal arch. This helps the foot keeping its natural position in the shoe and stimulates the musculature while walking. The slip-resistant textile cover is odour-resistant, moisture absorbing and washable at 30°C.
- **FAP® - Flexible Anti Perforation** - The flexible anti-perforation midsole made of ceramic-coated fibers, reliably protects the feet completely from penetrating objects.

Technical Data

| | |
|----------------------|---------|
| Color | -- |
| Sizes Available | -- |
| Packaging | -- |
| Packed | -- |
| Case Dimensions (in) | -- |
| Case Weight (lbs) | 0.00 |
| Country of Origin | China |
| Material | Textile |
| Outsole | -- |
| Toe Type | -- |
| Tread Pattern | -- |
| Height | -- |
| Construction | -- |
| Certifications | -- |
| Product Circularity | -- |

Performance Data

| | |
|------------------------|----|
| ASTM F2413 Requirement | -- |
|------------------------|----|

Care Instructions



Hand Wash



SKU Information

| SKU | COLOR | SIZE | UPC | UPC (INNER) | UPC (CASE) |
|-----|-------|------|-----|-------------|------------|
|-----|-------|------|-----|-------------|------------|